


**Inserti filettati a testa svasata in acciaio**  
**Acciaio Zincato C4C**



Tipo	d 6H	D mm	B mm	S m m	Ø foro mm	Spessori serrabili mm	L <sub>1</sub> min ÷ max	L mm	Trazione	Coppia max serraggio
<b>M3 TS-C</b> <b>M3 TS-L</b>	M3	4,9	8	1,5	5	1,5 ÷ 3,0 3,0 ÷ 4,0	4,7 ÷ 5,3	9,5 10,5	4000 N	1,20 Nm
<b>M4 TS-C</b> <b>M4 TS-L</b>	M4	5,9	9	1,5	6	1,5 ÷ 3,5 3,5 ÷ 5,0	5,8 ÷ 6,3	11 13	6000 N	3,8 Nm
<b>M5 TS-C</b> <b>M5 FS-L</b>	M5	6,9	10	1,5	7	1,5 ÷ 4,0 4,0 ÷ 6,0	6,3 ÷ 7,3	13 15	10000 N	6,00 Nm
<b>M6 TS-C</b> <b>M6 TS-L</b>	M6	8,9	12	1,5	9	1,5 ÷ 4,0 4,0 ÷ 6,0	8,5 ÷ 9,2	15 17	15000 N	11,50 Nm
<b>M8 TS-C</b> <b>M8 TS-L</b>	M8	10,9	14	1,5	11	1,5 ÷ 4,0 4,0 ÷ 6,0	9,5 ÷ 10,4	16,5 19	22500 N	22,00 Nm
<b>M10 TS-C</b> <b>M10 TS-L</b>	M10	11,9	15	1,5	12	1,5 ÷ 4,0 4,0 ÷ 6,0	11 ÷ 12	18 20,5	26000 N	37,00 Nm